

#### PRODUCT DATASHEET

# Recessed Panel light HYD-102R-9W 4000K



## **Application**

- Office
- Kitchen
- Rest room
- Corridor
- Shop

#### **Benefits**

- · Flicker free.
- The light is soft and bright
- Drive stable,safe and reliable
- High light transmission mask to ensure uniform light

#### **Features**

- Efficient and durable
- Easy and quick installation
- Light body thin design, reduce space occupancy
- Die-cast aluminum body for better heat dissipation, anti-corrosion, and easy maintain





## **Electrical Data**

Nominal wattage (W)	9W	
Nominal Voltage (V)	220-240 V	
Mains Frequency (Hz)	50	
Nominal Current (mA)	68	
LED Driver Current (mA)	250	
LED Driver Voltage (VDC)	30-42	
LED Driver Efficiency (%)	83%	
Power Factor λ	0.55C	
Total harmonic distortion (%)		
Operating mode	External LED Driver	

#### **Photometrical data**

Luminous flux ±10% (lm)	785 lm	
Luminous efficacy	93 lm/w	
Color temperature	4000K	
Light color (designation)	Natural White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤5 SDCM	
Luminous intensity/cd	280	
Flickering	Flicker free	
Beam angle	111 °	






Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

4000K



**Dimensions & Weight** 

Diameter (mm)	146
Height (mm)	35
Product weight (g)	219



## **Material & Colors**

Product color	All White	
Housing color	White	
Body material	Aluminum	
Cover material	PS LGP material	
Mercury content	0.0 mg	

**Application & Mounting** 

Ambient temperature range	-20°C~+50 °C	
Temperature range at storage	-25°C~+60 °C	
Type of connection	Screwless terminal	
Type of protection	IP20	
Dimmable	No	
Mounting type	Recesse mounted	
Mounting location	Ceiling	
Application environment	Indoor	
Cut size (mm)	130	
LED module replaceable	Not replaceable	
With light source	Yes	




**Certificates & Lifespan** 

Life (h)	50,000
Certificates	CB LVD EMC RoHS
Standards	ISO9001:2015

# **Logistical Data**

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-102R-9W	53*20*42.5 cm	30		0.04505

## **Installation Method**



### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.