

# **PRODUCT DATASHEET**

## Black lamp cup, enhanced anti-glare,Led spot light HYD-342AS-7W 6500K



# Application

- Home
- Restaurant
- Exhibition Hall
- Stage
- Conference Room
- Clothing Store

# **Benefits**

- Flicker free
- It can be used for emphasis lighting and decorative lighting
- Spot light have prominent advantages in commercial lighting
- No secondary light spot, it can create a wall washing effect

## Features

- Warranty 5 years
- PC,Good light transmission
- Small size, light weight, buckle design, easy to install
- Die-cast aluminum, good heat dissipation, reduce light decay

December,20,2023 Product Datasheet HYD-342AS-7W 6500K





#### **Electrical Data**

Nominal wattage (W)	7W	
Nominal Voltage (V)	220-240 V	
Mains Frequency (Hz)	50	
Nominal Current (mA)	68	
LED Driver Current (mA)	300	
LED Driver Voltage (VDC)	21-24	
LED Driver Efficiency (%)		
Power Factor λ	0.5	
Total harmonic distortion (%)		
Operating mode	External LED driver	

### **Photometrical data**

Luminous flux ±10% (lm)	447 lm		
Luminous efficacy	61 lm/w		
Color temperature	6500K		
Light color (designation)	Cold White		
Color rendering index Ra	≥80		
Standard deviation of color matching	≤5 SDCM		
Luminous intensity/cd	1533		
Flickering	Flicker free		
Beam angle	26 °		






IES

December,20,2023 Product Datasheet HYD-342AS-7W 6500K



## **Dimensions & Weight**

Diameter (mm)	85*85
Height (mm)	63
Product weight (g)	302



D

## **Material & Colors**

Product color	Black Lamp cup / White Housing		
Housing color	White		
Body material	Aluminum		
Cover material	PC		
Mercury content	0.0 mg		

## **Application & Mounting**

Ambient temperature range	-20°C~+45 °C		
Temperature range at storage	-25°C~+60 °C		
Type of connection	Screwless terminal		
Type of protection	IP20		
Dimmable	No		
Mounting type	Recessed		
Mounting location	Ceiling		
Application environment	Indoor		
Cut size (mm)	72*72		
LED module replaceable	Not replaceable		
With light source	Yes		



### **Certificates & Lifespan**


Life (h)	50,000		
Certificates	CB CE LVD EMC		
Standards	ISO9001:2015		

## Logistical Data

Product code	Dimensions	Pcs/	G.W.	Volume
	(L*W*H)	carton	kg	CBM
HYD-342AS-7W	•••			

This is the estimated data. Subject to the actual shipment.

## **Installation Method**



#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

December,20,2023 Product Datasheet HYD-342AS-7W 6500K